



FIGHTER

Fighter 1627 Euro 6.

4x2 / 6-SP MANUAL / STEEL or AIR SUSP.



OUR SAFEST FIGHTER YET WITH ACTIVE MITIGATION BRAKE, LANE DEPARTURE WARNING SYSTEM, ELECTRONIC STABILITY PROGRAM AND ACTIVE SIDEGUARD ASSIST AS STANDARD.

GVM

16,000_{KG}

GCM

19,500_{KG}

Power/Torque

199_{KW} / 785_{NM}

- Medium rigid licence required.
- Actual vehicle may differ from above image

FIGHTER SPECIFICATIONS

MODEL

A	4X2 1627 STEEL SUSP. SWB 6 SP. MAN - FM65FH6RFAH
B	4X2 1627 STEEL SUSP. XLWB 6 SP. MAN - FM65FM6RFAH
C	4X2 1627 STEEL SUSP. XXLWB 6 SP. MAN - FM65FS6RFAH
D	4X2 1627 AIR SUSP. XXLWB 6 SP. MAN - FM67FS6RFAH

WHEEL BASE

4280mm
5550mm
6500mm
6500mm

GVM


16,000kg
16,000kg
16,000kg
16,000kg

GCM

19,500kg
19,500kg
19,500kg
19,500kg

Engine

Engine Version	FUSO 6M60-CAT6 Diesel
Configuration	6 Cyl. In-line OHC, 4-Valve
Injection System	DENSO Common Rail System Electronically Controlled Direct Injection
Type	Variable Geometry Turbo Charged Air to Air Intercooler
Displacement	7.5 litre (7545cc)
Bore	118mm
Stroke	115mm
Power (ECE R85-00)	199kW @ 2500 rpm
Torque (ECE R85-00)	785Nm @ 1100-2400 rpm
Maximum Engine Speed	2900 rpm
Compression Ratio	16.0:1
Cooling System / Oil Cooler	Water cooled, 23.0L capacity/ Plate type engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Mounted Underbody (RH)
Emission Control	Diesel Particulate Filter (DPF) Exhaust Gas Recirculation (EGR) Selective Catalytic Reduction (SCR)
Emission Level	ADR 80/04 - Euro VI



Fuel

Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity *	A 200 Litres B C D 300 Litres
AdBlue Exhaust Fluid Capacity	49 Litres, Tank fitted with locking AdBlue cap
Speed Limiter	Speed Limited 100km/h
Notes	*Max Fill to approx 95% of capacity

Cooling

Fan Drive	Electronically controlled (Viscous)
Radiator	Corrugated Fin with Expansion Tank

Electrical

Voltage	24V Negative Earth
Battery Capacity	2x12V, 80Ah/5hr
Battery Specification	95E41R X2
Headlamp Type	Halogen
Headlamp Capacity	Low beam 2x70W High beam 2x70W
Fog Light	Halogen

Clutch

Clutch Model	FUSO C7M38
Type	Single Plate
Operation/Specification	Air Assisted Hydraulic

Transmission

Version	FUSO Manual M070S6-DD
Type/Speeds	6 with Air Assisted Gearshift
Features	Synchromesh 2nd-6th
Ratios	1st: 8.064 2nd: 5.443 3rd: 3.064 4th: 1.824 5th: 1.321 6th: 1.000 Rev. 7.354
PTO Opening	LH Side

Propeller Shaft

Type	P10
Universal Joint	Needle Roller

Front Axle

Axle Version	FUSO F650T
Type	Reverse Elliot 'I' Beam
Capacity *	6300kg
Notes	*See MAX LOADING for vehicle capacity.

Front Suspension

Type	Parabolic Leaf with Double Acting Shock Absorbers
Size	1400x80mm Leaves

Rear Axle

Type	Full Floating Banjo Type
Axle Version	FUSO R060T/D8H
Capacity*	10200kg
Ratio	A 5.142:1 B C D 4.444:1
Notes	*See MAX LOADING for vehicle capacity.

Rear Suspension

Type	A B C Steel Suspension D Air Suspension
Details	A B C Semi-Elliptic Leaf D Trailing Arm with Double Acting Shock Absorber and CLCS
Size Main Leaves	A B C 1400x80mm D N/A
Size Helper Leaves	A B C 960x80mm D N/A
Air Spring	A B C N/A D 2x250mm dia.
Trailing Arm	A B C N/A D 615+380 x 80 x 35 - 2 Leaves
Road Friendly Certification Number	A B C N/A D RF2043
Capacity at Ground *	A B C N/A D 10000kg total
Notes	CLCS - Chassis Level Control System. Electronic height control of air suspension via steering wheel. 2 memory positions.

FIGHTER SPECIFICATIONS

MODEL	WHEEL BASE	GVM	GCM
A 4X2 1627 STEEL SUSP. SWB 6 SP. MAN - FM65FH6RFAH	4280mm	16,000kg	19,500kg
B 4X2 1627 STEEL SUSP. XLWB 6 SP. MAN - FM65FM6RFAH	5550mm	16,000kg	19,500kg
C 4X2 1627 STEEL SUSP. XXLWB 6 SP. MAN - FM65FS6RFAH	6500mm	16,000kg	19,500kg
D 4X2 1627 AIR SUSP. XXLWB 6 SP. MAN - FM67FS6RFAH	6500mm	16,000kg	19,500kg

Max Loading

Front	6000kg
Rear	10000kg
Total	16000kg

Options

Options	R34: Limited Slip Differential - FM65FH R35: Engine Flywheel PTO - FM65FH Max. Output Torque, 300Nm Drive Ratio, 0.635:1 Rotation, Same as Engine.
---------	--

Steering

Type	Integral Power Assisted Ball and Nut
Steering Column	Tilt/Telescopic Adjustable

Brakes

Type	Full Air, Dual Circuit, FUSO Taper Roller, ABS, Automatic Brake Adjustment
Size Front	410x150mm
Size Rear	410x200mm
Park Brake	Rear Wheel Spring Actuated
Auxiliary	Exhaust Brake
Compressor	Water Cooled, 340cc Single Cyl.

Wheels & Tyres

Wheel Type	7 x Single Piece Steel Disc Including Spare		
Wheel Size	22.5x8.25DC-165-13t		
Wheel Stud Pattern	10x335mm PCD		
Tyre Size All	A	B C D	
	11R22.5 148/145L	275/70R22.5 148/145L	
Spare Tyre Carrier	Provided		

Chassis

Type	Parallel Channel
Size	280x90x8.0mm
Width	841mm
Tensile Strength	540 MPa

Instruments

Gauges	Speedometer Tachometer Fuel Level Air Pressure AdBlue Level
Colour Information Display	Odometer Tripmeter (x2) Hour Meter (x2) Outside Temperature AdBlue Level DPF Information Driving Range (Fuel and AdBlue) Current Vehicle Speed Cruise Control Lane Departure Warning Attention Assist Warning Alarm Clock Level Control Service Indicator & Reminder System Air Pressure Coolant Temperature Engine Oil Level & Running Time

Multi-Media Package

Satellite Navigation	GPS navigation specifically designed for commercial vehicle applications, with 3 years of Map updates included.
Colour Display	8" LCD with capacitive touch screen control
Phone Connectivity	Wireless Apple Carplay & Android Auto Compatible
Audio Visual Entertainment	Bluetooth® music streaming compatible Digital radio DAB+ (also AM/FM for areas not covered by DAB+) & USB
Internal Storage Capacity	64GB
Camera Compatibility	1 Reverse Camera fitted as standard Display can accept up to 5 additional cameras#
Notes	# Cameras available through spare parts

Active Safety

Safety Systems	A MB plus - Active Mitigation Brake ESP - Electronic Stability Program AA - Attention Assist ASA - Active Sideguard Assist LDWS - Lane Departure Warning System ABS - Anti-lock Braking System DRL - Daytime Running Lamps
Reverse Warning	Wide Dynamic Range Camera and Buzzer
Notes	Active Safety Systems primary function is to provide driver assistance to increase road safety in events of driver inattentiveness. These systems do not allow for lack of attention whilst driving and should not replace safe and alert driving.

Passive Safety

Airbags	SRS Airbag - Driver
Seat Belts	Driver Seat Belt Pre-tensioner

Service Intervals

Interval*	20,000km or 12 Months whichever occurs first
-----------	--

Warranty*

Basic/Powertrain	5 Years or 350,000kms (whichever occurs first)
------------------	--

Performance

Turning Circle (kerb to kerb - metres)	A	B	C D
	14.6	18.4	21.4
Electronically Speed Limited to:	100km/hr Conforms to ADR65/00		
Gradeability at Rated GVM (theoretical)*	A	B C D	
	36%	34%	
Notes	*This is theoretical performance only. Actual performance may vary under different conditions		

Mass estimated*

Front*	A	B	C	D
	2965kg	3040kg	3115kg	3120kg
Rear*	A	B	C	D
	1925kg	1905kg	1980kg	1935kg
Total*	A	B	C	D
	4890kg	4945kg	5095kg	5055kg
Notes	* Mass (est.) includes oil and water but excludes spare wheel, tools & fuel. Weights provided are subject to 3.5% variation (+/-)			

FIGHTER SPECIFICATIONS


MODEL	WHEEL BASE	GVM	GCM
A 4X2 1627 STEEL SUSP. SWB 6 SP. MAN - FM65FH6RFAH	4280mm	16,000kg	19,500kg
B 4X2 1627 STEEL SUSP. XLWB 6 SP. MAN - FM65FM6RFAH	5550mm	16,000kg	19,500kg
C 4X2 1627 STEEL SUSP. XXLWB 6 SP. MAN - FM65FS6RFAH	6500mm	16,000kg </td <td>19,500kg</td>	19,500kg
D 4X2 1627 AIR SUSP. XXLWB 6 SP. MAN - FM67FS6RFAH	6500mm	16,000kg	19,500kg

Dimensions mm

WFF (Width Front Fender) (mm)	2450		
WRA (Width Rear Axle) (mm)	2470		
WFT (Width Front Track) (mm)	1925		
WRT (Width Rear Track) (mm)	1850		
Width Frame (mm)	841		
A - Length Overall (mm)	A	B	C D
	7455	9325	10695
C - Front Overhang (mm)	1245		
D - Wheelbase (mm)	A	B	C D
	4280	5550	6500
G - Front Axle to Rear of Cab (mm)	745		
H - Rear of Cab to Rearmost Item Behind Cab (mm)	75		
I - Rearmost Item Behind Cab to Rear Axle (mm)	A	B	C D
	3460	4730	5680
J - Frame, Rear Axle to End (mm)	A	B	C D
	1930	2530	2950
P - Height Cab to Ground (mm)	A	B C D	
	2680	2630	
R - Height Rear Frame to Ground (mm)	A	B	C D
	1074	1033	1032 969

Body Builder's Notes

Notes	<p>Chassis reinforcement must be utilised for Tipper/ Demountable type body configurations.</p> <p>To conform with ADR 13/00 and 14/03 (lighting/mirror requirements) the following must be adhered to at body installation.</p> <ul style="list-style-type: none"> - If other than a flat type or tipper body is fitted, rear end out-line marker lamps must be installed. - If overall length exceeds 6.0 metres, side reflectors must be installed. - If overall length exceeds 7.5 metres, side marker lamps must be installed. - If overall width is less than 2.4 metres, the mirrors must be modified to project not more than 230mm. <p>To conform with ADR 42/05 (General Safety), rear wheel guards must be fitted to the vehicle.</p>
-------	--



Call 1800 033 557

or visit fuso.com.au

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this are for illustration purposes only and may not be available from Daimler Truck Australia Pacific Pty Ltd. ABN 86 618 413 282 DTAuP. No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTAuP. DTAuP reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTAuP please contact your authorised FUSO dealer. Fuso is a registered trademark of Daimler Truck Australia Pacific Pty Ltd. Copyright DTAuP. Reproduction in whole or part prohibited without written approval. Part Number TSF66A. Valid from 17-May-21.