

# FUSO

# CANTER

## CANTER 815

4X2 / WIDE CREW CAB / MANUAL OR DUONIC DCT



**OUR SAFEST CANTER EVER WITH AEBS, LDWS AND ESP STANDARD.  
CLASS LEADING 30,000KM SERVICE INTERVALS.**

**GVM**

**7,500<sub>KG</sub>**

**GCM**

**11,000<sub>KG</sub>**

**Power/Torque**

**110<sub>kW</sub> / 400<sub>Nm</sub>**

- Light rigid licence required. Can be derated and driven with a passenger car licence.
- Actual product may vary from image shown.

# CANTER SPECIFICATIONS

## MODEL

A	4X2 815 WIDE CREW CAB MWB 6 SP. DUONIC AMT (FEB71ER3WFBM)
B	4X2 815 WIDE CREW CAB LWB 6 SP. DUONIC AMT (FEB71GR3WFBM)
C	4X2 815 WIDE CREW CAB LWB 5 SP. MAN (FEB71GR4WFBM)

## WHEEL BASE

3400mm
3850mm
3850mm

## GVM (optional)


7,500kg (4,495kg)
7,500kg (4,495kg)
7,500kg (4,495kg)

## GCM (optional)

11,000kg (7,995kg)
11,000kg (7,995kg)
11,000kg (7,995kg)

## Engine

Engine Version	FUSO 4P10-T4 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Injection System	Bosch Common Rail Direct Injection Bosch Piezo Technology Injectors
Type	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Bore	95.8mm
Stroke	104mm
Power (DIN)	110kW @ 2626 rpm
Torque (DIN)	400Nm @ 1600-2626rpm
Maximum Engine Speed	4150 rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled, 13.7L capacity/ Plate type engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9
Emission Level	ADR 80/04 - Euro VI



## Fuel

Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity *	100 Litres
Filtration	Filter with Water Separator and Indicator Sensor
AdBlue Exhaust Fluid Capacity	12 Litres
Notes	*Max Fill to approx 95% of capacity

## Cooling

Fan Drive	Thermo modulated continuous control (Viscous)
Radiator	Corrugated Fin with Expansion Tank

## Electrical

Voltage	12V Negative Earth
Battery Capacity	2x12V, 70Ah/5hr
Battery Specification	115D31L x2
Headlamp Type	LED
Body Builder Harness	Yes

## Clutch

Clutch Model	<b>A B</b> Fully Automated Dual Clutch (no clutch pedal)	<b>C</b> FUSO C4W30
Type	<b>A B</b> Dual Clutch (Wet Multi-plate)	<b>C</b> Single Dry Plate, Direct Hydraulic Type

## Transmission

Version	<b>A B</b> FUSO DUONIC M038S6	<b>C</b> FUSO M038S5
Type/Speeds	<b>A B</b> 6 Speed Dual Clutch with Auto and Manual Modes	<b>C</b> 5 Speed with In-Dash Gearshift Lever
Features	<b>A B</b> Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage	<b>C</b> Synchromesh 1st-5th
Ratios	<b>A B</b> 1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev. 5.397	<b>C</b> 1st: 5.494 2nd: 3.038 3rd: 1.592 4th: 1.000 5th: 0.723 Rev. 5.494
PTO Opening	LH Side	

## Front Axle

Axle Version	FUSO F350T
Type	Reverse Elliot 'I' Beam
Capacity *	3100kg
Notes	*See MAX LOADING for vehicle capacity.

## Front Suspension

Type	Multi-Leaf with Stabiliser Bar and Double Acting Shock Absorbers
Size	1150x70mm Leaves

## Rear Axle

Type	Full Floating Banjo Type	
Axle Version	FUSO R035T	
Capacity*	6000kg	
Ratio	<b>A B</b> 5.714:1	<b>C</b> 5.285:1
Notes	*See MAX LOADING for vehicle capacity.	

## Rear Suspension

Type	Steel Suspension
Details	Semi-Elliptic Leaf with Stabiliser Bar and Double Acting Shock Absorbers
Size Main Leaves	1250x70mm
Size Helper Leaves	880x70mm

## Max Loading

Front	3100kg
Rear	6000kg
Total	7500kg

# CANTER SPECIFICATIONS

## MODEL

A	4X2 815 WIDE CREW CAB MWB 6 SP. DUONIC AMT (FEB71ER3WFBM)
B	4X2 815 WIDE CREW CAB LWB 6 SP. DUONIC AMT (FEB71GR3WFBM)
C	4X2 815 WIDE CREW CAB LWB 5 SP. MAN (FEB71GR4WFBM)

## WHEEL BASE

3400mm
3850mm
3850mm

## GVM (optional)

7,500kg (4,495kg)
7,500kg (4,495kg)
7,500kg (4,495kg)

## GCM (optional)

11,000kg (7,995kg)
11,000kg (7,995kg)
11,000kg (7,995kg)

## Options

Options	H31: 4495/7995kg GVM/GCM Rating
---------	---------------------------------

## Steering

Type	Integral Ball and Nut Type
Steering Column	Tilt/Telescopic Adjustable
Power Assist	Standard

## Brakes

Type	Hydraulic Dual Circuit with Front and Rear Discs Twin Calliper Front and Rear
Size Front	252x40mm
Size Rear	252x40mm
Features	ABS plus EBD (Electronic Brake Distribution) Active Emergency Braking System (AEBS) Electronic Stability Program (ESP) Exhaust Brake Electronic Brake Wear Sensors
Park Brake	Transmission Mounted

## Wheels & Tyres

Wheel Type	7 x Single Piece Disc Rims (Including Spare)
Wheel Size	17.5x6.0-127
Wheel Stud Pattern	6 Stud 222.25 PCD
Tyre Size All	215/75R17.5 124/123
Spare Tyre Carrier	Provided

## Chassis

Type	Reinforced Tapered Channel
Size	192x60x6mm
Width	752mm
Tensile Strength	440 MPa

## Instruments

Gauges	Speedometer with Odometer Tachometer Fuel Level Water Temperature
Colour Information Display	Fuel Consumption DPF Bar Chart from 1~9 Water Temperature Lane Departure Warning Maintenance Reminder System Tripmeters

## Multi-Media Package

Satellite Navigation	GPS navigation specifically designed for commercial vehicle applications, with 3 years of Map updates included.
Colour Display	8" LCD with capacitive touch screen control
Phone Connectivity	Wireless Apple Carplay & Android Auto Compatible
Audio Visual Entertainment	Bluetooth® music streaming compatible Digital radio DAB+ (also AM/FM for areas not covered by DAB+) & USB
Camera Compatibility	1 Reverse Camera fitted as standard Display can accept up to 5 additional cameras#
Notes	# Cameras available through spare parts

## Standard Features

Airbag(s)	Dual Air Bags and Seat Belt Pre-Tensioners (Driver & Far Side Passenger)
Active Safety Features	ABS plus Electronic Brake force Distribution (EBD) Advanced Emergency Braking (AEBS) Anti-Slip Regulator (ASR) Electronic Stability Program (ESP) Lane Departure Warning System (LDWS)
Cruise Control	A B C Yes No
Hill Start System	Yes
Cab Cooling & Heating	Air Conditioner / Heater / Demister. Rear crew air conditioner and heater with separate control
Accessory Power	12V Accessory Power Outlet / Cigar Lighter
Driving	Fuso Multimedia Unit Keyless Central Locking Electric Windows (front only) Cup Holders (2)
Storage	Dual Overhead Storage Pockets Lockable Storage Under Rear Crew Seats In-Dash Centre Document Storage Door Storage Pockets Dash Storage Tray (1 DIN)
Cab: External	Front End-Outline Marker Lamps Door Side Impact Beams (front only)
Chassis	Reverse Warning Buzzer Factory Reverse Camera with Infrared Display and Audible Pickup (Supply only in Cabin with Cab Chassis)

## Cab Features

Type	Steel Fixed Cab
Cab Structure	ECE-R29 European Cab Strength Approved
Mounting	6 Point Isolated Rubber
Additional Engine Access	Removable Engine Access Panel
Colour	Natural White
Windscreen Wipers	2 Speed + Intermittent Cycle with Integrated Washer Nozzles
Rear Vision Mirrors	1 x Internal 2 x External Convex (ECE 46) - Heated
Seating Capacity	7
Seat Belts	4 x Lap Sash Belts and Head Rests for Outside Seating 3 x Lap Belts for Centre Seat Drivers Seat Belt Warning (From Aug 20 build)
Seat (driver)	Suspended with Weight Adjustment, LH Arm Rest and Lumbar Support
Seats (passenger)	Flat Folding, 2 Passenger Bench for Front Passengers
Seats (crew cab rear)	Low Back Bench Seat

## Service Intervals

Interval*	30,000km or 12 Months (whichever occurs first)
-----------	--

## Warranty\*

Basic/Powertrain	5 Years or 200,000kms (whichever occurs first)
Cab Perforation/Anti Corrosion	5 Years
Notes	* Please refer to Fuso Owners Warranty Booklet for additional terms and conditions.

## Performance

Turning Circle (kerb to kerb - metres)	A 12.2	B C 13.6
Road Speed (km/h) at Max Engine Speed	127	
Engine Speed (rpm) at 100km/hr (top gear)	2817	
Gradeability at Rated GVM (theoretical)*	34.5%	
Notes	*This is theoretical performance only. Actual performance may vary under different conditions	

# CANTER SPECIFICATIONS

## MODEL

A	4X2 815 WIDE CREW CAB MWB 6 SP. DUONIC AMT (FEB71ER3WFBM)
B	4X2 815 WIDE CREW CAB LWB 6 SP. DUONIC AMT (FEB71GR3WFBM)
C	4X2 815 WIDE CREW CAB LWB 5 SP. MAN (FEB71GR4WFBM)

## WHEEL BASE

3400mm
3850mm
3850mm

## GVM (optional)

7,500kg (4,495kg)
7,500kg (4,495kg)
7,500kg (4,495kg)


## GCM (optional)

11,000kg (7,995kg)
11,000kg (7,995kg)
11,000kg (7,995kg)

Mass estimated*			
Front*	A	B	C
	1750kg	1770kg	1740kg
Rear*	A	B C	
	920kg	915kg	
Total*	A	B	C
	2670kg	2685kg	2655kg
Notes	* Mass (est.) includes oil and water but excludes spare wheel, tools & fuel. Weights provided are subject to 3.5% variation (+/-)		

Dimensions mm			
WFF (Width Front Fender) (mm)	1995		
WRA (Width Rear Axle) (mm)	2030		
WRT (Width Rear Track) (mm)	1560		
Width Frame (mm)	750		
A - Length Overall (mm)	A	B C	
	5935	6685	
C - Front Overhang (mm)	1140		
D - Wheelbase (mm)	A	B C	
	3400	3850	
G - Front Axle to Rear of Cab (mm)	1525		
H - Rear of Cab to Rearmost Item Behind Cab (mm)	54		
I - Rearmost Item Behind Cab to Rear Axle (mm)	A	B C	
	1821	2271	
J - Frame, Rear Axle to End (mm)	A	B C	
	1395	1695	
P - Height Cab to Ground (mm)	2220		
Q - Height Cab to Frame (mm)	1514		
R - Height Rear Frame to Ground (mm)	A	B C	
	795	794	

Body Builder's Notes	
Notes	<p>Chassis reinforcement must be utilised for Tipper/ Demountable type body configurations.</p> <p>To conform with ADR 13/00 and 14/02 (lighting/mirror requirements) the following must be adhered to at body installation.</p> <ul style="list-style-type: none"> <li>- If overall width exceeds 2.1 metres and other than flat type or tipper body is fitted, rear end-outline markers must be installed.</li> <li>- If overall length exceeds 6.0 metres, side reflectors must be installed.</li> <li>- If overall length exceeds 7.5 metres and width exceeds 2.1 metres, side marker lamps must be installed.</li> <li>- If overall width is less than 1.9 metres (for city cab) or 2.2 metres (for wide cabs), the mirrors must be modified to project not more than 230mm.</li> </ul> <p>To conform with ADR 42/04 (General Safety), rear wheel guards must be fitted to the vehicle.</p>



Call 1800 033 557

or visit [fuso.com.au](http://fuso.com.au)

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this are for illustration purposes only and may not be available from Daimler Truck Australia Pacific Pty Ltd. ABN 86 618 413 282 DTB. No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTB. DTB reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTB please contact your authorised FUSO Truck and Bus dealer. Fuso is a registered trademark of Daimler Truck and Bus Australia Pacific Pty Ltd. Copyright DTB. Reproduction in whole or part prohibited without written approval. Valid from 25-Feb-25.